



## Art of the Analog Console



### ProSpec™ - 2U6M2S Audio Mixers

#### FEATURE OVERVIEW:

- Live Performance contracting mixers designed to operate in Mono, Stereo, or LCR applications.
- 6 Channels of Burr-Brown Microphone Pre-Amplifiers and 2 multiple input stereo line input channels.
- Balanced Left, Right, Center and Aux XLR outputs and dual Sum mono outputs use THAT Corporation Out-Smarts devices.
- Individual Solo and Channel On switches on each mono and stereo input channel.
- Each input channel is assignable to Left-Right or Center mix bus
- Mono input channels have High and Low Frequency EQ with Variable High Pass Filter.
- Stereo input channels have High and Low Frequency EQ with fixed High-Pass Filter
- Individual Left, Right, Center and Aux Output Metering with Limiter active LED indicators.
- Mono input channel use Neutrik XLR/1/4" combo connectors and TRS insert and Direct Output connectors.
- Stereo input use individual 1/4" balanced left and right input connectors, RCA Inputs and (Stereo Input Channel 1) USB Digital or (Stereo Input Channel 2) front panel stereo input 1/8" connector.
- Low phase-shift, wide bandwidth electronic design derived from APB's Spectra and ProDesk products.
- Designed and Manufactured in the U.S.A. See [www.apb-dynasonics.com](http://www.apb-dynasonics.com) for additional information.

